



# **Hybrid Coatings for Highest Standards**



Particularly in the automotive sector, the standards keep rising when it comes to optical appearance, quality, and individualization options. Mara® Cure HY Hybrid Coatings are up to this task thanks to the combined benefits of solvent-based and UV-curable coatings: Flexibility and resistance!

Especially in the IMD (In-mould Decoration) or FIM (Film Insert Moulding) technology there is a process-related need for high temperature resistance and flexibility during moulding, while the finished product must feature highest mechanical and chemical resistance.

Mara<sup>®</sup> Cure HY is a flexible, abrasion and chemical resistant Dual-Cure screen print varnish which can be used as surface protection or as a so-called "Hard Coat" for films made of PC, PMMA, or ABS which are susceptible to abrasion.

## **Applications**

As a modern and economical alternative to film coating, Mara® Cure HY is suited for all IMD process steps on substrates commonly used in the automotive sector like polycarbonate (PC), PMMA, and ABS.

Characteristics Mara® Cure HY	
High flexibility	✓
Very good adhesion	✓
High resistances	✓
Silicone-free (HY 911)	✓

For further information please refer to the Technical Data Sheet on <a href="https://www.marabu-inks.com">www.marabu-inks.com</a>

### **Your Benefits:**

## During the IMD-/FIM process

- → High flexibility of the varnish guarantees best mouldability
- → High temperature resistance
- → Economical, efficient alternative to film coating!

#### After the manufacturing

- → Excellent chemical resistance,
  e. g. sunscreen resistance conforming to GMW
  14445
- → Outstanding mechanical resistance,
  e. g. according to Oesterle DBL 9202
- → Very good adhesion and scratch resistance

## Versatile use

- → Protective coatings or eye-catching effects: Use the glossy varnish for glossy effects on matt surfaces, or vice versa, create matt effects on glossy surfaces with the satin transparent varnish
- → Different degrees of gloss possible

In the event of any queries, please contact:

Technical Hotline

Phone: +49 7141 691140, technical.hotline@marabu.de